

## CNC4230 – 1.3M Mini POE Weatherproof IR IP Camera



**1.3 Mega**

**30 IR LED**

**3D-DNR**

**Dual Stream**

**IP66**

**TDN**

**POE**

**ONVIF**

### Features

- 1.3 Megapixel 1280x960 @25fps
- H.264 High Profile
- ONVIF compatible
- 4 / 6mm Fixed Lens
- 3D-DNR, Dual Stream
- Day&Night by Filter Change
- 30 IR LED, 0 Lux up to 20m
- Network 10/100 Base-T
- IE, Firefox, Chrome support
- Android, iPhone/iPad application
- 256ch CMS Software included
- IP66 Weatherproof

### SPECIFICATION

Model	CNC4230
Image Sensor	1/3" progressive scan CMOS Sensor
Resolution	1280x960 @25fps (PAL) or 30fps (NTSC)
Shuttle	1/25s ~ 1/100,000s
Lens	M12 4/6mm Fixed Lens
LEDs	30nos 850nm IR LED
Day & Night	Filter Change or TDN (True Day & Night)
Minimum Illumination	0 Lux up to 20m
Network	10/100-BaseT, RJ45
Bit Rate	32Kbps ~ 16Mbps
Compression	Dual Stream : H.264 High Profile / MJPEG
Working Environment	-10° ~ +60°C, <90° Humidity (Non-Condensing)
Power	POE IEEE 802.3af compliant, or 12VDC, Max. 5.5W (IR-On)
Dimension	60mm(φ) x 140mm(L), 300g

\* Specification maybe changed without prior notice