

**WG4024**

User-friendly release with personalised Nice key or standard lock (optional)

Exclusive, patented layout of the internal components

Exclusive, patented layout of the internal components

<p><b>FLO2R-S</b></p>	<p><b>MC424L</b></p>	<p><b>MOF</b></p>
<p><b>MOSE</b></p>	<p><b>ML24T</b></p>	<p><b>PLA13 TS</b></p>

**The kit contains:**

**WG4024** 2 surface-mounted electromechanical gear motors, with Nice key release.  
**FLO2R-S** 1 transmitter 433.92 MHz, 2 channels. **MC424L** 1 control unit with SMXI plug-in receiver.  
**MOF** 1 pair of photocells for outdoor installation. **MOSE** 1 key selector switch for outdoor installation.  
**ML24T** 1 flashing light with integrated aerial. **PLA13** 2 travel stops for opening manoeuvres.  
**TS** 1 signboard.

**For swing gates with leaves up to 2 m, surface mounted.**  
 24 Vdc electromechanical gear motor.

**Reliable and silent:**  
 patented layout of internal parts, fewer moving parts.

**Easy to install:** after the gear motor has been assembled, all electrical connections are made from above.

**User-friendly release** with personalised Nice key or standard lock (optional).

**Pre-assembled,** travel stops PLA13 on opening.

**Moonclever control unit MC424L:**

- simple programming, by means of a single key;
- clutch with anti-crush safety feature;
- automatic memorization of limit switches on opening and closing with self-learning function;
- programming of pause time;
- pedestrian pass door;
- deceleration on opening and closing;
- obstacle detection system;
- can be linked to the 8.2 KOhm resistive sensitive edge;
- continues to work even during power failures using optional (PS124) batteries that fit inside the control unit.

Code	Description	Pack/pallet
<b>WINGO4024KCE</b>	Kit for swing gates with leaves up to 2 m, 24 Vdc, surface mounted	12

**N.B.** The content of the package may vary: consult the retailer.

**Technical specifications**

Code	WG4024
<b>Electrical data</b>	
Power supply (Vdc)	24
Absorption (A)	3.5
Power (W)	85
<b>Performance data</b>	
Speed (m/s)	0.018
Force (N)	1500
Work cycle (cycles/hour)	30
<b>Dimensional and general data</b>	
Protection level (IP)	44
Working temp. (°C Min/Max)	-20 ÷ +50
Dimensions (mm)	770x98x95 h
Weight (kg)	17

**Utilisation limits**

